

We Claim:

1. A printer having at least one inkjet printhead which comprises  
a substrate;  
a plurality of nozzles positioned on the substrate, each nozzle comprising  
5 a nozzle chamber and an aperture through which ink from the nozzle chamber is ejected;  
an actuator that is operatively positioned with respect to the nozzle chamber for causing ejection  
of ink within the nozzle chamber from the aperture; and  
drive circuitry arranged on the substrate and connected to the actuator to control operation of the  
actuator;  
10 wherein the drive circuitry and the actuator of each nozzle extend over a common portion of the  
substrate.
2. The printer of claim 1 wherein the actuator comprises a thermal actuator incorporating a heating  
circuit, and wherein the drive circuitry is adapted to provide an electrical current to said heating circuit.
- 15 3. The printer of claim 2 wherein the thermal actuator includes a paddle disposed within the nozzle  
chamber and being connected to a lever arm for pivotal movement of the paddle within the nozzle  
chamber.
- 20 4. The printer of claim 1 wherein the substrate is a silicon wafer.
5. The printer of claim 1 wherein the actuator is at least partially external to the nozzle chamber.
6. The printer of claim 1 wherein the drive circuitry and the actuator overlap in plan view.
- 25 7. An inkjet printhead which comprises  
a substrate;  
a plurality of nozzles positioned on the substrate, each nozzle comprising  
a nozzle chamber and an aperture through which ink from the nozzle chamber is ejected;  
30 an actuator that is operatively positioned with respect to the nozzle chamber for causing ejection  
of ink within the nozzle chamber from the aperture; and  
drive circuitry arranged on the substrate and connected to the actuator to control operation of the  
actuator;  
wherein the drive circuitry and the actuator of each nozzle extend over a common portion of the  
35 substrate.
8. The printhead of claim 7 wherein the actuator comprises a thermal actuator incorporating a heating  
circuit, and wherein the drive circuitry is adapted to provide an electrical current to said heating circuit.
- 40 9. The printhead of claim 8 wherein the thermal actuator includes a paddle disposed within the nozzle

chamber and being connected to a lever arm for pivotal movement of the paddle within the nozzle chamber.

5

10. The printhead of claim 7 wherein the substrate is a silicon wafer.
11. The printhead of claim 7 wherein the actuator is at least partially external to the nozzle chamber.
12. The printhead of claim 7 wherein the drive circuitry and the actuator overlap in plan view.